


Page 1/12

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31





Page 2/12

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 19.03.2024

Version number 11 (replaces version 10)

Revision: 08.08.2023

Trade name: STAMCOLL N55

(Contd. of page 1) · Signal word Danger · Hazard-determining components of labelling: acetone ethyl acetate Butanone · Hazard statements H225 Highly flammable liquid and vapour. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness. · Precautionary statements P210 Keep away from flames and hot surfaces. No smoking. P241 Use explosion-proof [electrical/ventilating/lighting] equipment. P261 Avoid breathing vapours. P280 Wear protective gloves / eye protection. P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. · 2.3 Other hazards · Results of PBT and vPvB assessment · PBT: Not applicable.

• **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· Description: Adhesive

· Dangerous components:

 CAS: 67-64-1
 acetone
 >25-≤50%

 EINECS: 200-662-2
 Image: Flam. Liq. 2, H225; Image: Eye Irrit. 2, H319; STOT SE 3, H336,
 >25-≤50%

 Reg.nr.: 01-2119471330-49 EUH066
 Eye Irrit. 2, H319; STOT SE 3, H336,
 >25-≤50%

 CAS: 78-93-3
 Butanone

 EINECS: 201-159-0
 Image: Eline Constraints

 Reg.nr.: 01-2119457290-43
 Flam. Liq. 2, H225; Eline Constraints

 European Constraints
 Flam. Liq. 2, H225; Eline Constraints

 Eline Constraints
 Flam. Liq. 2, H225; Eli

· Additional information For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

• 4.1 Description of first aid measures

• After inhalation Supply fresh air; consult doctor in case of complaints.

• After skin contact Clean with water and soap. If possible, also wash with polyethylene glycol 400.

(Contd. on page 3)

GB

>5-<10%



Page 3/12

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 19.03.2024

Version number 11 (replaces version 10)

Revision: 08.08.2023

(Contd. of page 2)

Trade name: STAMCOLL N55

· After eye contact

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- *After swallowing* Do not induce vomiting; call for medical help immediately.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- Suitable extinguishing agents

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam. Use fire extinguishing methods suitable to surrounding conditions.

· For safety reasons unsuitable extinguishing agents Water with full jet

• 5.2 Special hazards arising from the substance or mixture

- Formation of toxic gases is possible during heating or in case of fire.
- 5.3 Advice for firefighters
- · Protective equipment: Wear self-contained respiratory protective device.
- Additional information Cool endangered receptacles with water spray.

SECTION 6: Accidental release measures

 6.1 Personal precautions, protective equipment and emergency procedures Ensure adequate ventilation
 Wear protective equipment. Keep unprotected persons away.
 Keep away from ignition sources.
 6.2 Environmental precautions:

- Do not allow product to reach sewage system or any water course. Prevent seepage into sewage system, workpits and cellars.
- 6.3 Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to section 13. Ensure adequate ventilation.
- Do not flush with water or aqueous cleansing agents
- · 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

• 7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace. • Information about protection against explosions and fires:



Keep ignition sources away - Do not smoke.

(Contd. on page 4)



Page 4/12

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 19.03.2024

Version number 11 (replaces version 10)

Revision: 08.08.2023

(Contd. of page 3)

Trade name: STAMCOLL N55

Protect against electrostatic charges. Protect from heat.

- 7.2 Conditions for safe storage, including any incompatibilities
- · Storage
- Requirements to be met by storerooms and containers: Store in a cool location.
- Information about storage in one common storage facility: Not required.
- \cdot Further information about storage conditions:
- Keep receptacle tightly sealed.
- Store in cool, dry conditions in well sealed receptacles.
- 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

• Components with critical values that require monitoring at the workplace:

67-64-1 acetone

WEL Short-term value: 3620 mg/m³, 1500 ppm Long-term value: 1210 mg/m³, 500 ppm

141-78-6 ethyl acetate

WEL Short-term value: 1468 mg/m³, 400 ppm Long-term value: 734 mg/m³, 200 ppm

78-93-3 Butanone

WEL Short-term value: 899 mg/m³, 300 ppm Long-term value: 600 mg/m³, 200 ppm Sk, BMGV

· DNELs

67-64-1 acetone

Oral DNEL 62 mg/kg/day (general population (long-term)) Dermal DNEL 62 mg/kg/day (general population (long-term)) 186 mg/kg/day (workers (Long-term)) Inhalative DNEL 200 mg/m³ (general population (long-term))

- 2,420 mg/m³ (workers (Short-term))
- 1,210 mg/m³ (workers (Long-term))

141-78-6 ethyl acetate

Oral DNEL 4.5 mg/kg/day (consumers (Long-term))

- Dermal DNEL 37 mg/kg/day (consumers (Long-term))
 - 63 mg/kg/day (workers (Long-term))
- Inhalative DNEL 734 mg/m³ (consumers (Short-term))
 - 367 mg/m³ (consumers (Long-term))
 - 1,468 mg/m³ (workers (Short-term))
 - 734 mg/m³ (workers (Long-term))

(Contd. on page 5)



Page 5/12

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 19.03.2024 Version number 11 (replaces version 10) Revision: 08.08.2023 Trade name: STAMCOLL N55 (Contd. of page 4) 78-93-3 Butanone Oral DNEL 31 mg/kg/day (general population (long-term)) Dermal DNEL 412 mg/kg/day (general population (long-term)) 1,161 mg/kg/day (workers (Long-term)) Inhalative DNEL 106 mg/m³/day (general population (long-term)) 600 mg/m³/day (workers (Long-term)) · PNECs 67-64-1 acetone PNEC 10.6 mg/l (Freshwater) 1.06 mg/l (Sea water) 21 mg/l (Water - partially release) 100 mg/l (Sewage treatment plants (STP)) PNEC 29.5 mg/kg (Soil) 3.04 mg/kg (Sediment (Sea water)) 30.4 mg/kg (Sediment (Freshwater)) 141-78-6 ethyl acetate PNEC 0.24 mg/l (Freshwater) 0.024 mg/l (Sea water) 0.115 mg/l (Sediment (Sea water)) 1.15 mg/l (Sediment (Freshwater)) 650 mg/l (Purification plant) 1.65 mg/l (Water) PNEC 0.148 mg/kg (Soil) 78-93-3 Butanone PNEC 55.8 mg/l (Freshwater) 55.8 mg/l (Sea water) 709 mg/l (Purification plant) PNEC 22.5 mg/kg (Soil) 287.7 mg/kg (Sediment (Sea water)) 284.7 mg/kg (Sediment (Freshwater)) · Ingredients with biological limit values: 78-93-3 Butanone BMGV 70 µmol/L Medium: urine Sampling time: post shift Parameter: butan-2-one · Additional information: The lists valid during the making were used as basis. · 8.2 Exposure controls • Appropriate engineering controls No further data; see section 7.

(Contd. on page 6)

GB —



Page 6/12


Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Version number 11 (replaces version 10)

Revision: 08.08.2023

Trade name: STAMCOLL N55

Printing date 19.03.2024



SECTION 9: Physical and chemical properties

General Information		
Physical state	Fluid	
Colour:	Opaque	
Smell:	Characteristic	
Odour threshold:	Not determined.	
Melting point/freezing point:	Undetermined.	
Boiling point or initial boiling point and	boiling	
range	55 °C	
Flammability	Highly flammable.	
Lower and upper explosion limit		
Lower:	2.1 Vol %	
		(Contd. on page 7)

GB –



Page 7/12

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 19.03.2024

Version number 11 (replaces version 10)

Revision: 08.08.2023

Trade name: STAMCOLL N55

	(Contd. of page
Upper:	13 Vol %
Flash point:	-18 °C
Auto-ignition temperature:	375 °C
Decomposition temperature:	Not determined.
pH	Mixture is non-soluble (in water).
Viscosity:	
Kinematic viscosity	Not determined.
kinematic (calculated) at 40°C:	
dynamic at 20 °C:	2,300 mPas (ISO 2555)
Solubility	
Water:	Not miscible or difficult to mix.
Partition coefficient n-octanol/water (log value)	Not determined.
Steam pressure at 20 °C:	247 hPa
Density and/or relative density	
Density at 20 °C	0.85 g/cm ³ (EN ISO 2811-1)
Relative density	Not determined.
Vapour density	Not determined.
9.2 Other information	
Appearance:	
Appearance. Form:	Fluid
I orm. Important information on protection of health an	
environment, and on safety.	u
Self-inflammability:	Product is not selfigniting.
Seij-injtammability: Explosive properties:	Product is not explosive. However, formation of
Explosive properties.	
Organia solvants.	explosive air/vapour mixtures are possible. 65.3 %
Organic solvents: VOC	65.3 %
Solids content:	34.7 % (DIN EN 827.8.2)
Change in condition	Not dataminad
Evaporation rate	Not determined.
Information with regard to physical hazard classe	S
Explosives	Void
Flammable gases	Void
Aerosols	Void
Oxidising gases	Void
Gases under pressure	Void
Flammable liquids	Highly flammable liquid and vapour.
Flammable solids	Void
Self-reactive substances and mixtures	Void
Pyrophoric liquids	Void
Pyrophoric solids	Void
Self-heating substances and mixtures	Void
Substances and mixtures, which emit flammable	
gases in contact with water	Void
Oxidising liquids	Void
Oxidising solids	Void
Organic peroxides	Void
Corrosive to metals	Void
construction metallo	, 0.00



Page 8/12

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 19.03.2024 Version number 11 (replaces version 10)

Revision: 08.08.2023

(Contd. of page 7)

Trade name: STAMCOLL N55

· Desensitised explosives

Void

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

10.2 Chemical stability

• Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

· 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

• Acute toxicity Based on available data, the classification criteria are not met.

• LD/LC50 values that are relevant for classification:

67-64-1 acetone

 Oral
 LD50
 5,800 mg/kg (Rat) (OECD RL 401)

 Dermal
 LD50
 >15,800 mg/kg (Rat)

 Inhalative
 LC50/4h 76 mg/l (Rat)

141-78-6 ethyl acetate

 Oral
 LD50
 5,620 mg/kg (Rat)

 Dermal
 LD50
 >20,000 mg/kg (rabbit)

 Inhalative
 LC50/8h 58 mg/l (Rat)

78-93-3 Butanone

Oral LD50 3,300 mg/kg (Rat) Dermal LD50 >8,000 mg/kg (Rabbit)

Inhalative LC50/4h 10,000 mg/l (Rat)

- Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- *Reproductive toxicity Based on available data, the classification criteria are not met.*
- STOT-single exposure
- May cause drowsiness or dizziness.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.
- 11.2 Information on other hazards
- Endocrine disrupting properties

None of the ingredients is listed.

(Contd. on page 9)



Page 9/12

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 19.03.2024

Version number 11 (replaces version 10)

Revision: 08.08.2023

Trade name: STAMCOLL N55

(Contd. of page 8)

12.1 Toxic Aquatic to	•	
67-64-1 ac		
NOEC/16h	1,700 mg/l (Pseudomonas putida)	
	4,740 mg/l (algae)	
	11,300 mg/l (Leuciscus idus) (DIN 38412 T.15)	
	5,540 mg/l (Oncorhynchus mykiss)	
	8,300 mg/l (Lepomis macrochirus)	
LC50/48h	12,600 mg/l (Daphnia magna)	
	11,300 mg/l (Leuciscus idus)	
EC5/16h	1,700 mg/l (Pseudomonas putida)	
EC5/72h	28 mg/l (Entosiphon sulcatum)	
EC5/8d	530 mg/l (Microcystis aerruginosa)	
EC50/18h	12,600–12,700 mg/l (Daphnia magna)	
EC50/48h	6,100 mg/l (Daphnia magna)	
EC50/96h	8,300 mg/l (Lepomis macrochirus)	
141-78-6 е	thyl acetate	
LC50/96h	230 mg/l (Pimephales promelas)	
LC50/48h	333 mg/l (Leuciscus idus)	
EC10/18h	2,900 mg/l (Pseudomonas putida)	
EC50/48h	3,300 mg/l (Scenedesmus subspicatus)	
	717 mg/l (Daphnia magna)	
78-93-3 Bi	itanone	
LC50/96h	3,220 mg/l (Pimephales promelas)	
EC5/16h	1,150 mg/l (Pseudomonas putida)	
IC5/7d	1,300 mg/l (algas)	
12.2 Persis 12.3 Bioac 12.4 Mobi	>100 mg/l (Daphnia magna) stence and degradability No further relevant information available. scumulative potential No further relevant information available. lity in soil No further relevant information available. ts of PBT and vPvB assessment applicable.	
	applicable.	
	c rine disrupting properties ct does not contain substances with endocrine disrupting properties.	
	adverse effects	
	ecological information:	
General no		
water haze	ard class 1 (German Regulation) (Self-assessment): slightly hazardous for water	



Page 10/12

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 19.03.2024

Version number 11 (replaces version 10)

Revision: 08.08.2023

Trade name: STAMCOLL N55

(Contd. of page 9) Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system. Must be specially treated adhering to official regulations.

· Uncleaned packagings:

• Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information

SECTION 14. Transport injormal		
· 14.1 UN number or ID number		
· ADR, IMDG, IATA	UN1133	
· 14.2 UN proper shipping name		
ADR	1133 ADHESIVES	
· IMDG, IATA	ADHESIVES	
· 14.3 Transport hazard class(es)		
· ADR, IMDG, IATA		
· Class	3 Flammable liquids.	
· Label	3	
· 14.4 Packing group		
· ADR, IMDĞ, IATA	III	
· 14.5 Environmental hazards:	Not applicable.	
· Marine pollutant:	nein	
· 14.6 Special precautions for user	Warning: Flammable liquids.	
· Kemler Number:	-	
· EMS Number:	F- E , S - D	
· Stowage Category	A	
· 14.7 Maritime transport in bulk according	g to IMO	
instruments	Not applicable.	
· Transport/Additional information:		
· ADR		
· Limited quantities (LQ)	5L	
\cdot Excepted quantities ($\widetilde{E}Q$)	Code: E1	
	Maximum net quantity per inner packaging: 30 ml	
	Maximum net quantity per outer packaging: 1000 ml	
· Transport category	3	
• Tunnel restriction code	Ε	
	(Contd. on page 11	



Page 11/12

(Contd. of page 10)

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Revision: 08.08.2023

Printing date 19.03.2024

Version number 11 (replaces version 10)

Trade name: STAMCOLL N55

- ·IMDG
- · Limited quantities (LQ)
- · Excepted quantities (EQ)

5LCode: El

· UN "Model Regulation":

Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml UN 1133 ADHESIVES, 3, III

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- · Poisons Act
- · Regulated explosives precursors

None of the ingredients is listed.

· Regulated poisons

None of the ingredients is listed. · Reportable explosives precursors

67-64-1 acetone: Listed

Reportable poisons

None of the ingredients is listed.

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t

· National regulations

VOC (EU) 554.5 g/l

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

EUH066 Repeated exposure may cause skin dryness or cracking.

· Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

DNEL: Derived No-Effect Level (UK REACH)

(Contd. on page 12)



Page 12/12

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 19.03.2024

Version number 11 (replaces version 10)

Revision: 08.08.2023

Trade name: STAMCOLL N55

(Contd. of page 11)

GB

PNEC: Predicted No-Effect Concentration (UK REACH) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 2: Flammable liquids – Category 2 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3